

#### DOWN RIVER EQUIPMENT COMPANY

12100 W. 52<sup>nd</sup> Ave. Wheat Ridge, CO 80033 www.downriverequip.com Tel. 303.467.9489 Fax. 303.940.8812 Toll Free Tel. 888.467.2144

### **BOAT REPAIR BASICS**

- Shore Adhesive: One part glue for hypalon material (Down River, Avon, Hyside, Riken, etc...)
- LA 4123 PVC Adhesive: One part glue for PVC material (Aire, Star, JPW, etc...)
- Bostik Adhesive: One part glue for a wide range of materials
- Stabond Adhesive: Two part glue for all materials of boats (Glue & accelerator packaged with proportionate amounts of each)
- Tolulene: Cleaner for Hypalon material (Can be used on PVC as a heavy duty cleaner)
- MEK: Chemically prepares PVC to adhere to the glue (NOT a cleaner)

#### Directions for Hypalon repair:

- Mark area to be repaired on the boat
- Clean & buff/roughen both the boat and the patch
- Clean both surfaces with Tolulene
- Apply as then a coat of glue as possible to both the patch and the boat. Let this dry completely (1/2 to 1 hour)
- Apply second coat, again as thin as possible, let dry until tacky (5-10 mins)
- Place patch on boat. Using a roller rasp, roll from inside out all air bubbles (you can't really over roll the repair)

#### Directions for PVC repair:

- Mark area to be repaired on the boat
- Clean boat and patch
- Apply MEK to boat & patch, keep in lines of patch
- Apply as thin a coat of glue as possible to both the patch and the boat, let this completely dry (1/2 to 1 hour)
- Apply second coat, again as thin as possible, let dry until tacky (5-10 minutes)
- Place patch on the boat. Using a roller rasp, roll from inside out all air bubbles (you can't really over roll the repair)

#### Additional suggested items to add to your repair kit

- Scissors
- Spare Valve
- Valve Tool
- Frame Parts
  - Patch Material
  - D-Rings

- Oar Lock
- Beer

## \*\*\*MAKE SURE ALL CAPS ON GLUE ARE SECURED TIGHTLY\*\*\*

# **HAPPY BOATING!!!**